

CBB61 Metallized Film Capacitor

CBB61 金屬化薄膜電容器



產品認證(Safety Certification) :



產品特點：金屬化聚丙稀、損耗小、電容量穩定性好、阻燃塑料外殼, 阻燃環氧樹脂封裝，廣泛用於單相交流電機的起動和運行。

The feature: LOW loss, electric capacity stability, Flame-resistant shell, flame-resistant epoxy resin seal. The capacitor is widely uses in the single phase AC electrical machinery's starting and the revolution.

技術特性(Technical Specification) :

| | | |
|------------------------------|--|--------------------|
| 電容型號(Capacitance Type) | CBB61 , CBB6-1 | |
| 氣候類別(Climatic Category) | 40/70/21 , 40/85/21 | |
| 額定電額(Rated Voltage) | 250Vac~630Vac | |
| 電容量範圍(Capacitance Range) | 0.1~60μF | |
| 電容量偏差(Capacitance Tolerance) | J(±5%); K(±10%) , 或按客戶要求(According to customer requirements) | |
| 耐電壓(Withstand Voltage) | 引出端之間 (T-T) | 1.5Un 10s 或 2Un 2s |
| | 極殼之間(T-C) | ≥2000VAC 2S |
| 損耗角正切(Dissipation Factor) | ≤0.002(50/60Hz 20°C) | |
| 絕緣電阻(Insulation Resistance) | 引出端之間 (T-T) | ≥3000s |
| | 極殼之間 (T-C) | ≥1000MΩ |
| 安全等級(Safety Class) | P0 , P2, CYWT8 | |
| 壽命等級(Life Class) | C(3000h) , B(10000h) | |

Victor (HK) Development Co. 匯達(香港)發展公司
 Rm.1702 King Centre, 23 Dundas Street, Mongkok, Hong Kong
 香港 旺角 登打士街 23 號 嘉興商業中心 1702 室
 Tel: 852 2626-9193 Fax:852 2626-9229
 Email: sales@hk-victor.com Website: www.hk-victor.com