


HD-X2 Interference Suppression Capacitor

HD-X2 金屬化聚丙烯膜抗干擾安規電容器

HD-X2 Metallized Polypropylene Film Interference Suppression Capacitor



產品特點：金屬化聚丙烯膜、能承受過壓衝擊、塑料外殼（UL94 V-0）、阻燃環氧填充，廣泛用於電源跨線路等抗干擾場合。

The feature: Metallized polypropylene structure, Withstanding overvoltage stressing, Plastic case (UL94 V-0), Epoxy resin sealing, Widely used in interference suppression circuit.

產品認證(Safety Certification)：



技術特性(Technical Specification)：

氣候類別/阻燃等級 Climatic Category/Passive Flammability Class	40/85/21 C (GPF) 40/105/21 C (GMF)
額定電額 Rated Voltage	275Va.c./250Va.c. 50/60Hz
電容量範圍 Capacitance Range	0.01 μ F~10 μ F
電容器類別 Class	X2 / HD-X2
電容量偏差 Capacitance Tolerance	K (\pm 10%)
耐電壓：電極之間 Test voltage：Between Terminals	4.3UR(Vdc.),2s
絕緣電阻：電極之間 Insulation Resistance：Between Terminals	C \leq 0.3 μ F，R \geq 15000M Ω (100Vdc) C $>$ 0.3 μ F，R·C \geq 5000s (100Vdc)
損耗角正切 Dissipation Factor	C \leq 0.1 μ F $\tan\delta\leq$ 0.0015 (10kHz)
	0.1 μ F $<$ C \leq 1 μ F $\tan\delta\leq$ 0.0030 (10kHz)
	C $>$ 1 μ F $\tan\delta\leq$ 0.0010 (1kHz)

Victor (HK) Development Co. 匯達(香港)發展公司
Rm.1702 King Centre, 23 Dundas Street, Mongkok, Hong Kong
香港 旺角 登打士街 23 號 嘉興商業中心 1702 室
Tel: 852 2626-9193 Fax:852 2626-9229
Email: sales@hk-victor.com Website: www.hk-victor.com